


123-9906

Yeni Ürün
New Product



- Minimum kapı genişliği 580 mm olmalıdır.
- Min. Door width 580 mm



- Sistem üzerinde çift yöne yavaşlatıcı mevcuttur.
- The system has two way soft closing.

2X 123-9906-1410-500	1X 123-9906-1410-501	1X 123-9906-1410-502	2X 117-6958-1600-500	1X 123-9906-1420-505	2X 123-9906-1420-503
--	--	--	--	---	--

150-7006-1411

150-7007-1411

Technical drawing of the door assembly showing side and top views with dimensions.

Side View Dimensions:

- Top flange width: 46 mm
- Top flange height: 50 mm
- Top flange offset: 20 mm
- Door height: LW
- Door height formula: $DOOR\ LENGTH = LW + 5\ (mm)$
- Door height formula: $DOOR\ LENGTH = HX + 25\ (mm)$
- Min. 8 mm (indicated on the door profile)
- Max. 10 mm (indicated on the door profile)
- Bottom flange height: 10 mm
- Bottom flange width: 61 mm

Top View Dimensions:

- Min. 65 mm (indicated on the left side of the door)
- Min. 580 mm (indicated on the bottom of the door)

Ölçülerde değişiklik yapma hakkı saklıdır. Reserves the right to the change of the dimensions.

Kod / Code No	Açıklama / Description	Renk / Colour	Birim / Unit			Profil mt. / Profiles mt.			Bağ / Bnd.
123-9906-1410	60 Kg Yavaşlatıcılı Sürme Cam Kapı Sistemi / Sliding Glass Door System	Gri / Grey	1 Kapı / 1 Kit	4	192	-	-	-	-
150-7006-1411	Alüminyum Üst Ray Profili / Aluminium Top Rail Profile	Eloksal / Mat Anodized	mt.	-	-	2,0	3,0	-	6 ad/pcs
150-7007-1411	Alüminyum Alın Kapama Profili / Aluminum Covering Profile	Eloksal / Mat Anodized	mt.	-	-	2,0	3,0	-	6 ad/pcs